

(12) UK Patent Application (19) GB (11) 2 363 554 (13) A

(43) Date of Printing by UK Office 19.12.2001

(21) Application No 0118583.4

(22) Date of Filing 26.01.2000

(30) Priority Data

(31) 9901368 (32) 05.02.1999 (33) FR

(86) International Application Data
PCT/EP00/00592 En 26.01.2000

(87) International Publication Data
WO00/46616 En 10.08.2000

(51) INT CL⁷
E21B 47/12

(52) UK CL (Edition S)
H4P PPD
U1S S1248 S2207

(56) Documents Cited by ISA
EP 0028296 A US 4862425 A US 4398271 A
US 4276619 A

(58) Field of Search by ISA
INT CL⁷ E21B , G01R , G01V , H04B , H04L

(71) Applicant(s)
Schlumberger Holdings Limited
(Incorporated in the British Virgin Islands)
PO Box 71, Craigmuir Chambers, Road Town, Tortola,
British Virgin Islands


(74) Agent and/or Address for Service
Brian D Stooile
WesternGeco Limited, Schlumberger House,
Buckingham Gate, GATWICK, West Sussex, RH6 0NZ,
United Kingdom

(72) Inventor(s)
Guy Vachon

(54) Abstract Title

A method of saving a string of tools installed in an oil well, and a corresponding transmission assembly

(57) In order to ensure that at least some of the tools (12-1) to 12-4) in a string of tools that is permanently installed in an oil well (10) are kept in operation even in the event of a localized fault, the link (18) interconnecting the tools and a surface installation (16) is subdivided into segments by switch members (20). More precisely, a switch member is associated with each tool. In addition, the link (18) forms a loop with both ends thereof being connected to the surface installation (16).



GB 2 363 554 A

THIS PAGE BLANK (USPTO)




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : G01V 13/00, 11/00	A1	(11) International Publication Number: WO 00/46616 (43) International Publication Date: 10 August 2000 (10.08.00)
(21) International Application Number: PCT/EP00/00592 (22) International Filing Date: 26 January 2000 (26.01.00) (30) Priority Data: 99/01368 5 February 1999 (05.02.99) FR (71) Applicant (for all designated States except GB US): SCHLUMBERGER TECHNOLOGY B.V. [NL/NL]; Parkstraat 83-89, NL-2514 JG The Hague (NL). (71) Applicant (for GB only): SCHLUMBERGER HOLDINGS LIMITED [-/-]; P.O. Box 71, Craigmuir Chambers, Road Town, Tortola (VG). (71) Applicant (for FR only): SERVICES PETROLIERS SCHLUMBERGER [FR/FR]; 42, rue Saint Dominique, F-75007 Paris (FR). (72) Inventor; and (75) Inventor/Applicant (for US only): VACHON, Guy [US/US]; 1402 Falcon Ledge Drive, Austin, TX 78746 (US). (74) Agent: MENES, Catherine; Etudes & Productions Schlum- berger, 26, rue de la Cavée, Boîte postale 202, F-92142 Clamart Cedex (FR).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: A METHOD OF SAVING A STRING OF TOOLS INSTALLED IN AN OIL WELL, AND A CORRESPONDING TRANSMISSION ASSEMBLY		

(57) Abstract

In order to ensure that at least some of the tools (12-1) to 12-4) in a string of tools that is permanently installed in an oil well (10) are kept in operation even in the event of a localized fault, the link (18) interconnecting the tools and a surface installation (16) is subdivided into segments by switch members (20). More precisely, a switch member is associated with each tool. In addition, the link (18) forms a loop with both ends thereof being connected to the surface installation (16).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

A METHOD OF SAVING A STRING OF TOOLS INSTALLED IN AN OIL WELL, AND A CORRESPONDING TRANSMISSION ASSEMBLY

DESCRIPTION

Technical field

5 The invention relates to a method designed to enable at least a portion of a string of tools permanently installed in an oil well such as a production well to be saved in the event of a fault localized on one of the tools or on an electric cable connecting a surface
10 installation to each of the tools in series.

 The invention also relates to a transmission assembly including an electric cable connecting a surface installation in series to each of the tools of a string of tools installed permanently in an oil well, and
15 organized so as to enable such a method to be implemented.

State of the art

 In an oil well, a string of tools is generally
20 installed permanently for the purpose of measuring and controlling various characteristic magnitudes of the well. Such a string of tools comprises a certain number of tools disposed in the well one above another at determined depths. Each tool is independent of the
25 others and is provided in particular with means for measuring one or more magnitudes, or with means for controlling the flow of petroleum fluid along the well, or indeed with measurement means and with associated control means.

30 As a general rule, an electric cable connects a surface installation in series to each of the tools in a string of tools constituted in this way. The electric cable serves both to feed electricity to each of the tools and to transmit electrical signals from the surface
35 installation to each of the tools, and vice versa.

 In an existing arrangement, the link comprises two twisted conductors housed in a stainless steel tube. In

the surface installation, and also in each of the tools, signals are transmitted and received via a transformer. Electrical power is then supplied in common mode.

5 In that arrangement, which is characterized by a serial electrical link between the surface installation and the various tools, an interruption of an electrical conductor or the appearance of a short circuit will have the consequence of making the entire string of tools inoperative.

10

Summary of the invention

A specific object of the invention is to provide a method enabling at least a portion of a string of tools installed in an oil well to be saved in spite of a short
15 circuit or an interruption occurring in the cable or in one of the tools.

According to the invention, this result is obtained by means of a method of saving a string of tools installed in an oil well in the event of a localized
20 fault, a link connecting a surface installation in series with each of the tools of said string, the method being characterized in that it consists in subdividing the link into segments that are successively interconnected by switch means, in locating a fault, if any, by closing
25 each of the switch means one after another starting from the surface installation until said fault appears, and in closing only those switch means that precede the last-closed switch means.

Because of the presence of switching means on the
30 link, it becomes possible to save that portion of the string of tools which is situated above the location where the fault has occurred, by leaving open the lowest switching means connecting the surface installation to the faulty tool or segment.

35 In a preferred implementation of the invention, a link is used that forms a loop between the surface installation and the tools. Said fault is located by

closing the switch means in both directions along said loop from the surface installation, and in each direction only the switch means preceding the last-closed switch means are closed.

5 Preferably, switch means are associated with each of the tools.

Advantageously, each tool is caused to communicate separately with each of the two segments that are interconnected by the switch means associated with said
10 tool.

By means of these characteristics in combination, it is possible either to keep all of the tools in operation when the fault has occurred on a segment interconnecting two tools, or else to put only one of the tools out of
15 circuit when the fault has occurred within said tool.

In a preferred implementation of the invention, the link comprises an electric cable. In which case, advantageously, the tools are powered in common mode while signals are simultaneously being interchanged
20 between the surface installation and each of the tools over a two-conductor cable.

The invention also provides a link connecting a surface installation in series with each of the tools of a string of tools installed in an oil well, which
25 assembly is characterized in that the link is made up of successive segments that are interconnected by switch means suitable for being opened to isolate at least one faulty tool or cable segment.

30 **Brief description of the drawings**

A preferred embodiment of the invention is described below by way of non-limiting example with reference to the accompanying drawings, in which:

• Figure 1 is a diagrammatic vertical section view
35 showing a transmission assembly of the invention associated with a string of tools permanently installed in a borehole; and

Figure 2 is a view comparable to Figure 1, showing a variant implementation of the transmission assembly.

Detailed description of a preferred embodiment of the invention

In Figure 1, reference 10 designates an oil well in production.

A string of tools is placed in the oil well 10 to perform measurement and control therein for well-operating purposes. In the embodiment shown by way of example, the string of tools comprises four tools numbered 12-1 to 12-4 starting from the surface and installed in the well at different depths, one above another.

As shown for the tool 12-3 only, in order to simplify Figure 1, each of the tools 12-1 to 12-4 has an active portion 14. Depending on the nature of the tool in question, the active portion 14 may have one or more sensor(s), one or more actuator(s), or both sensors and actuators. The tool also includes an electronics module serving to transmit signals in one direction or the other and also to transmit various commands.

The tools 12-1 to 12-4 are interconnected and are also connected to a surface installation 16 by means of an electric cable 18. In the embodiment shown, the electric cable 18 has two, preferably twisted-together, electrical conductors 19 disposed inside a stainless steel tube (not shown) for protecting the electrical conductors 19.

More precisely, the link 18 connects the surface installation 16 in series to each of the tools 12-1 to 12-4, and in this case does so in the same order as the order in which the tools were installed inside the well 10.

As shown solely for the tool 12-3, to simplify the figure, switch means 20 are associated with each of the tools 12-1 to 12-4 so as to subdivide the link 18 into

successive segments that are interconnected by the switch means 20.

In the embodiment shown where the cable 18 has two electrical conductors 19, each of the switch means 20 has two switches each located in a respective one of the electrical conductors.

At a first end of the cable 18, the two electrical conductors 19 are connected to the secondary winding of a transformer 22 that forms part of the surface installation 16. The primary winding of the transformer 22 is connected to signal transmitter means 23 and receiver means 24.

The surface installation 16 also has a common mode electrical power supply source 25 connected to the midpoint of the secondary winding of the transformer 22. Means for closing the electrical power supply circuit are represented diagrammatically by a switch 26.

As shown solely for the tool 12-3, to simplify Figure 1, each of the tools 12-1 to 12-4 includes a transformer 28 whose primary winding is electrically connected between the electrical conductors 19 of the cable 18, upstream from the switch means 20 of the tool in question, i.e. vertically towards the top of the well relative to said switch means. The secondary winding of the transformer 28 fitted to each of the tools is electrically connected to the active portion 14 associated with said tool via transmitter means 30 and receiver means 29.

Each transformer 28, in association with the link 18, thus serves to transmit signals between the surface installation 16 and the tool in question. More precisely, each transformer 28 serves to transmit signals from the surface installation 16 to the active portion 14 of the corresponding tool. Conversely, each transformer 28 also serves to transmit signals from the corresponding tool 12-1 to 12-4 to the surface installation 16.

In addition, each of the tools 12-1 to 12-4 has an electrical power supply circuit 32 connected to the midpoint of the primary winding of the transformer 28 associated with the tool. The assembly thus makes it possible to power each of the tools 12-1 to 12-4 in common mode from an electrical power supply source 25 located in the surface installation 16.

The transmission assembly described above makes it possible, in the event of a short circuit or of an interruption occurring in one of the tools or in one of the segments of the cable 18 between two tools, to save all of the tools that are situated above the faulty element.

Thus, assuming that a short circuit or an interruption has occurred on the segment of cable 18 that interconnects the tools 12-3 and 12-4, then the tools 12-1 to 12-3 can be kept in action by closing the switch means associated with the tools 12-1 and 12-2 and by opening the switch means 20 associated with the tool 12-3. In which case only the tool 12-4 is inoperative.

Assuming that the interruption or short circuit has taken place inside one of the tools, such as the tool 12-3, then all of the tools situated thereabove can continue to be used, by leaving the switch means 20 associated with the tool 12-2 open and by closing the switch means associated with the tools situated thereabove, i.e. in this case the tools 12-1. On this assumption, all of the tools situated above the faulty tool can continue to be used, while the faulty tool and the tools situated beneath it are inoperative.

In the absence of a fault, all of the switch means 20 are normally closed, as is the switch 26. Under such circumstances, all of the tools 12-1 to 12-4 are operative.

When a fault occurs, it is immediately detected by the signal transmitter means 23 and receiver means 24 connected to the secondary winding of the transformer 22.

A command to open the switch 26 and all of the switch means 20 is then issued.

The fault is then located by closing the switch means 20 associated with each of the tools 12-1 to 12-4 one after another until the fault reappears.

More precisely, signals are sent to the first tool 12-1 from the surface to find out whether it is operating properly. When the surface installation receives signals confirming such proper operation, the switch means 20 associated with this first tool are closed.

If this closure causes the fault to reappear, then the fault is located either in the segment of cable 18 interconnecting the tools 12-1 and 12-2, or else in the tool 12-2. Under such circumstances, none of the switch means 20 can be kept in the closed state, and only the tool 12-1 remains usable.

Otherwise, i.e. if no fault occurs when the switch means 20 associated with the first tool 12-1 is closed, then the operations previously performed on the tool 12-1 are repeated on the following tool 12-2. When the tool 12-2 is found to be in working order, the corresponding switch means 20 are closed.

As before, this closure can either cause the fault to reappear, or can give rise to no new fault.

These operations are repeated step by step until the fault is indeed located. After the previously closed switch 26 and switching means 20 have been opened again, the switch 26 is reclosed as are all of the switch means 20 preceding the previously last-closed switch means that led to the fault being detected.

In Figure 1, there is shown a preferred embodiment of the invention which provides considerably more effective tool saving. To this end, the link 18 is not terminated at the deepest tool 12-4, but hereafter rises back up the well to the surface installation 16. In other words, the link 18 forms a loop going from the surface installation 16 via each of the tools 12-1 to 12-

4 in succession, and then returning to the surface installation 16.

In this case, and as shown diagrammatically in Figure 1, the surface installation 16 is arranged so as to enable the tools 12-1 to 12-4 to be powered and so as to enable signals to be transmitted via either of the two ends of the cable 18 that are connected to the installation 16. To this end, the surface installation 16 has a second transformer 22' whose secondary winding is connected to the second end of the cable 18 and is connected across its two electrical conductors 19. The primary winding of the transformer 22' is connected to signal transmitter means 23' and receiver means 24'.

To enable each of the tools 12-1 to 12-4 to be powered electrically from the second end of the cable 18, the midpoint of the secondary winding of the transformer 22' is electrically connected to an electrical power supply source 25' via means for closing the power supply circuit and represented by a switch 26'.

It should be observed that in practice, the various elements of the surface installation 16 connected to each of the ends of the electric cable 18 can have various portions in common, unlike the diagrammatic illustration of Figure 1.

In this preferred embodiment of the invention, each of the tools 12-1 to 12-4 also has means enabling electrical power to be delivered and electrical signals to be transmitted downstream of the switch means 20 fitted to the tool in question.

Thus, and as shown solely for the tool 12-3, in order to simplify the figure, each of the tools then includes a second transformer 28' whose primary winding is connected between the two electrical conductors of the cable 18 downstream from the switch means 20 of the tool in question, i.e. beneath the switch means. The secondary winding of each of the transformers 28' is then connected to the active portion 14 of the stage in

question via transmitter means 30' and receiver means 29'. This arrangement makes it possible to ensure that signals can be transmitted in either direction between the elements of the surface installation 16 connected to the second end of the cable 18 and the tool in question, even when the switch means 20 of the tool in question are open.

In addition, the midpoint of the primary winding of the transformer 28' associated with each of the tools is connected to electrical power supply means 32' of the tool in question. This arrangement makes it possible to power the tool electrically from the second end of the cable 18 when the switch means 20 fitted to the tool are open.

In this preferred embodiment of the invention, all of the tools can be kept active in the event of a short circuit or an interruption occurring in any one of the segments of the cable 18 interconnecting any two tools 12-1 to 12-4. The switch means 20 of two of the tools such as 12-2 and 12-3 situated at opposite ends of the segment in question are then put into the open state while all of the other switch means are closed. Under such conditions, the tools such as 12-1 and 12-2 situated above the faulty cable segment are powered and electrically connected to the surface installation 16 via the portion of the cable 18 that is situated above the faulty segment. In addition, the tools such as 12-3 and 12-4 that are situated beneath the faulty segment are electrically powered and connected to the surface installation 16 via the other portion of the cable 18, connecting the bottom tool 12-4 to the surface installation.

If the fault lies within one of the tools, such as the tool 12-2, then all of other tools, i.e. in this case the tools 12-1, 12-3, and 12-4, can be kept in working order.

To this end, the switch means 20 associated with the tools adjacent to the faulty tool, such as 12-1 and 12-3 in this case, are kept open while the other switch means 20 are kept closed, e.g. the switch means associated with the tool 12-4, with this being done by acting on the corresponding end of the cable.

The procedure is identical to that described above when the cable 18 does not form a loop. The only exception is that it is effected in this case from each of the two ends of the cable 18.

In the embodiment described with reference to Figure 1, the tools 12-1 to 12-4 of the string of tools installed in the well 10 are connected in series in the same order as that with which they are to be found inside the well. However, in a variant, as shown diagrammatically in Figure 2, this method of connection is merely one particular non-limiting example.

Thus, in Figure 2, the first end of the cable 18 from the surface installation 16 connects said assembly in series successively to the top tool 12-1, to the tool 12-3, then to the tool 12-4, prior to coming back up the well via the tool 12-2 and up to the surface installation 16.

Any other mode of serial connection involving all of the tools in the string of tools, regardless of how many tools are involved, could be adopted without going beyond the ambit of the invention.

It should be observed that although it is preferred to power all of the tools in common mode as described above, it is also possible to power the tools separately from signal transmission by providing the cable with a third electrical conductor. Under such circumstances, each switch means will also have a switch placed in said third conductor.

On the same lines, the technique used for transmitting signals between the surface installation and each of the tools can also be replaced by any equivalent

technique without going beyond the ambit of the invention.

Finally, the invention is not limited to the case where the tools and the surface installation are
5 interconnected by an electric cable. On the contrary, it applies to any type of link, for example a hydraulic link.

CLAIMS

- 1/ A method of saving a string of tools installed in an oil well in the event of a localized fault, a link (18) connecting a surface installation (16) in series with each of the tools (12-1 to 12-4) of said string, the method being characterized in that it consists in subdividing the link (18) into segments that are successively interconnected by switch means (20), in locating a fault, if any, by closing each of the switch means (20) one after another starting from the surface installation (16) until said fault appears, and in closing only those switch means (20) that precede the last-closed switch means.
- 2/ A method according to claim 1, in which a link (18) is used that forms a loop between the surface installation (16) and the tools (12-1 to 12-4), said fault is located by closing the switch means in both directions along said loop from the surface installation (16), and in each direction only the switch means preceding the last-closed switch means are closed.
- 3/ A method according to claim 1 or 2, in which switch means (20) are associated with each of the tools (12-1 to 12-4).
- 4/ A method according to claims 2 and 3 in combination, in which each tool (12-1 to 12-4) is caused to communicate separately with each of the two segments that are interconnected by the switch means (20) associated with said tool.
- 5/ A method according to any preceding claim, in which said link comprises an electric cable (18).
- 6/ A method according to claim 5, in which tools are powered in common mode while signals are simultaneously

interchanged between the surface installation (16) and each of the tools (12-1 to 12-4) over a two-conductor cable (18).

5 7/ A transmission assembly comprising a link (18) connecting a surface installation (16) in series with each of the tools (12-1 to 12-4) of a string of tools installed in an oil well (10), which assembly is characterized in that the link (18) is made up of
10 successive segments that are interconnected by switch means (20) suitable for being opened to isolate at least one faulty tool or cable segment.

8/ An assembly according to claim 7, in which the link
15 (18) forms a loop between the surface installation (16) and the tools (12-1 to 12-4).

9/ An assembly according to claim 7 or 8, in which respective switch means (20) are associated with each of
20 the tools (12-1 to 12-4).

10/ An assembly according to claims 8 and 9 in combination, in which each tool (12-1 to 12-4) communicates separately with each of two segments
25 interconnected by the switch means (20) associated with said tool.

11/ An assembly according to any one of claims 7 to 10, in which said link comprises an electric cable (18).
30

12/ An assembly according to claim 11, in which the cable (18) has two conductors and the surface installation (16) has a transformer (22, 22') whose primary winding is connected to signal transmitter and receiver means and
35 whose secondary winding is connected in series between the two conductors of the cable, the surface installation

(16) also comprising an electricity source (25, 25') connected to the midpoint of the secondary winding.




FIG. 1




FIG. 2

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/00592

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G01V13/00 G01V11/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G01V E21B H04L H04B G01R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 862 425 A (CRETIN JACQUES ET AL) 29 August 1989 (1989-08-29) column 5, line 63 -column 6, line 13 ----	1,7
A	US 4 398 271 A (CRETIN JACQUES ET AL) 9 August 1983 (1983-08-09) column 7, line 59 -column 9, line 34 ----	1,7
A	EP 0 028 296 A (LICENTIA GMBH) 13 May 1981 (1981-05-13) claim 3 ----	1,7
A	US 4 276 619 A (RICKENBACKER JAMES E) 30 June 1981 (1981-06-30) column 2, line 42 - line 53 -----	1,7

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

16 March 2000

Date of mailing of the international search report

22/03/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Häusser, T

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 00/00592

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4862425	A	29-08-1989	FR 2613496 A	07-10-1988
			CA 1299724 A	28-04-1992
			CN 1013312 B	24-07-1991
			EP 0285519 A	05-10-1988
			JP 2733839 B	30-03-1998
			JP 63256883 A	24-10-1988
			NO 881442 A,B,	03-10-1988
US 4398271	A	09-08-1983	FR 2471088 A	12-06-1981
			CA 1159137 A	20-12-1983
			DE 3045987 A	03-09-1981
			GB 2067056 A,B	15-07-1981
			IT 1134596 B	13-08-1986
			JP 1678116 C	13-07-1992
			JP 3035637 B	28-05-1991
			JP 56097891 A	06-08-1981
			NL 8006637 A	01-07-1981
			NO 803683 A,B,	09-06-1981
EP 0028296	A	13-05-1981	DE 2943979 A	07-05-1981
			NO 803182 A	04-05-1981
US 4276619	A	30-06-1981	NONE	